

Safety Data Sheet

VisiJet® M2S-HT250

Revision Date: June 29, 2020

1. IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the mixture: VisiJet M2S-HT250

1.2 Use of the preparation: For use with ProJet® 2500 systems

1.3 Company/undertaking identification:

3D Systems, Inc.
333 Three D Systems Circle
Rock Hill, South Carolina U.S.A.
Phone: 803.326.3900 or
Toll-free Phone: 800.793.3669
e-mail: moreinfo@3dsystems.com
Chemical Emergency:
800.424.9300 – Chemtrec

3D Systems Europe Ltd.
200 Maylands Avenue
Hemel Hempstead
Herts, HP2 7TG United Kingdom
Phone: +44 144-2282600
e-mail: moreinfo@3dsystems.com
Chemical Emergency:
+1 703.527.3887 - Chemtrec

3D Systems Asia-Pacific
30-32 Ceylon St
Nunawading VIC 3131
Australia
+61 3 9819 4422
e-mail: moreinfo@3dsystems.com
Chemical Emergency:
+(61) 29037.2994 – Aus Chemtrec

2. HAZARDS IDENTIFICATION

2.1 Classification

GHS : Regulation (EC) No. 1272/2008, 29 CFR 1910:

Physical Hazard:

None

Health Hazard:

| | | |
|--------------------|------------|------|
| Skin Sensitization | Category 1 | H317 |
|--------------------|------------|------|

Environmental Hazard:

| | | |
|--------------------------|------------|------|
| Chronic Aquatic Toxicity | Category 2 | H411 |
|--------------------------|------------|------|

2.2 Label Elements

Regulation (EC) No, 1272/2008:

Hazard pictograms and signal word:



GHS07



GHS09

Signal word: Warning

Hazard determining components of labelling:

Contains: diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide; 2-Propenoic acid, 2-methyl-, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, rel-; 2-Propenoic acid, 1,1'-[(octahydro-4,7-methano-1H-indene-5,7-diyl)bis(methylene)] ester

Hazard statements:

H317: May cause an allergic skin reaction

H411: Harmful to aquatic life with long lasting effects

Supplemental Hazard Statements:

Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation

Safety Data Sheet

VisiJet[®] M2S-HT250

Revision Date: June 29, 2020

Precautionary statements:

Prevention:

P261: Avoid breathing
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P273: Avoid release to the environment.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P321: Specific treatment (Wash contaminated skin with soap and water. Wash eyes with clean water for about 15 minutes).
P362: Take off contaminated clothing and wash before reuse
P391: Collect spillage.

Storage:

None

Disposal:

P501: Dispose of contents/container in accordance with local/state/regional regulations

Supplementary information:

Potential Health Effects:

Effects due to processing releases or residual monomer: Irritating to eyes, respiratory system and skin. Possible cross sensitization with other acrylates and methacrylates.
Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure).

Storage recommendation:

Protect from sunlight. Store in a well-ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical characterization:

Description: Organic mixture

3.2 Dangerous components:

| Chemical name | CAS-number | EC-number | % | Classification Regulation (EC) 1272/2008 |
|--|------------|-----------|-------|---|
| 2-Propenoic acid, 1,1'-[(octahydro-4,7methano-1H-indene-5,?-diyl)bis(methylene)] ester | 42594-17-2 | 255-901-3 | 50-90 | Skin Sensitization Category 1 - H317 Aquatic Chronic Category 2 - H411 |
| 2-Propenoic acid, 2-methyl-, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, rel- | 7534-94-3 | 231-403-1 | 5-10 | Skin Corrosion/Irritation Category 2 - H315 Serious Eye Damage/Eye Irritation Category 2 - H319 STOT Single Exposure Category 3 - H335 Aquatic Chronic Category 3 - H412 |
| diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide | 75980-60-8 | 278-355-8 | 1-5 | Reproductive Toxicity Category 2 - H361 Skin Sensitization Category 1 - H317 Aquatic Chronic Category 2 - H411 |

4. FIRST AID MEASURES

4.1 General Information: Ensure that eyewash stations and safety showers are close to the workstation location.

4.2 In case of inhalation: May cause respiratory irritation. Move affected person to fresh air. If respiratory irritation occurs, if breathing becomes difficult seek medical attention immediately.

Safety Data Sheet

VisiJet® M2S-HT250

Revision Date: June 29, 2020

4.3 In case of skin contact: May cause irritation or sensitization by skin contact, including redness and/or swelling. Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.

4.4 In case of eye contact: Irritating to eyes. Causes redness, swelling and pain. Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.

4.5 In case of ingestion: Irritating to mouth, throat and stomach. If ingested, drink plenty of water and seek immediate medical attention. Do not induce vomiting.

4.6 Self-protection of the first aider: Put on appropriate protective equipment (see section 8). Move exposed person to fresh air. Remove contaminated clothing and shoes.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media: Water mist, dry chemical, carbon dioxide, or appropriate foam.

5.2 Extinguishing media which must not be used for safety reasons: High volume water jet.

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Thermal decomposition products can include CO₂, CO, NO_x and smoke.

5.4 Special protective equipment for fire-fighters: Wear full protective clothing, including helmet, self-contained positive-pressure or pressure demand breathing apparatus, protective clothing and facemask.

5.5 Additional information: Move container from area if it can be done without risk. Cool containers with water spray. Avoid inhalation of material or combustion by-products.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions: Keep unnecessary personnel away. Wear appropriate protective equipment and clothing. Consult expert immediately.

6.2 Environmental precautions: Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. In case of contamination of aquatic environment inform local authorities.

6.3 Methods for cleaning up: Wear appropriate protective equipment and clothing. Absorb spillage with suitable absorbent materials. Place all waste in an appropriate container for disposal. The material and its container must be disposed of as hazardous waste. Keep away from sources of ignition.

7. HANDLING AND STORAGE

7.1 Handling Provide adequate ventilation. Use suitable protective equipment. Avoid contact with skin and eyes. Do not breathe vapors or mist. Avoid ignition sources. Do not allow to enter drains or watercourses.

7.2 Storage: Store sealed in the original container at room temperature. Keep this material indoors in a cool, dry, well ventilated place. Store out of direct sunlight or UV light sources. Storage Temperature: below 35 °C / 95 °F. Storage class 10, environmentally hazardous liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure limit values:

General Product Information: No occupational exposure limits (PEL/TWA) have been established for this product.

8.2 Exposure controls

Technical measures to prevent exposure: Use only with machines that have exhaust ventilation capability.

Instructual measures to prevent exposure: When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.

Safety Data Sheet

VisiJet® M2S-HT250

Revision Date: June 29, 2020

Personal protection equipment:

Respiratory protection: If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided (e.g. 3M 6000 with organic vapor cartridge A2 or half mask 3M 4251).

Hand protection: Use impervious nitrile gloves.

Eye protection: Wear safety glasses or chemical goggles.

Body protection: Use apron and closed shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance:

Physical state: liquid

Colour: light yellow

Odour: mild acrylate

9.2 Important health, safety and environmental information

| | |
|---|----------------------|
| pH (20 °C): | NA |
| Melting point/range (°C): | NA |
| Boiling point/range (°C): | NA |
| Flash point (°C): | 97.5 |
| Ignition temperature (°C): | NA |
| Vapour pressure (°C): | NA |
| Density (g/cm³): | NA |
| Bulk density (kg/m³): | NA |
| Water solubility (20°C in g/l): | NA |
| Partition coefficient: | NA |
| n-Octanol/Water (log Po/w): | NA |
| Viscosity, dynamic (mPa s): | 800 - 1000 (@ 30 °C) |
| Dust explosion hazard: | NA |
| Explosion limits: | NA |

10. STABILITY AND REACTIVITY

10.1 Conditions to avoid: Avoid exposure to heat and light. Take necessary actions to avoid static electricity discharge.

10.2 Materials to avoid: Oxidizing materials, strong acids and strong bases.

10.3 Hazardous decomposition products: Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

11. TOXICOLOGICAL INFORMATION

11.1 Toxicokinetics, metabolism and distribution: NA

11.2 Acute effects (toxicity tests) – Formulation has not been tested

Acute toxicity of the components:

Irritation to skin and eye

Causes sensitisation

Corrosive to skin

11.3 Experiences made in practice: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

11.4 General remarks: Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Safety Data Sheet

VisiJet[®] M2S-HT250

Revision Date: June 29, 2020

12. Ecological information

12.1 Ecotoxicity: The aquatic toxicity of the product is unknown; however based on components, it is predicted that this material may be harmful to aquatic organisms or cause long-term adverse effects in the aquatic environment. Prevent contamination of soil, drains and surface waters.

12.2 Mobility: No information available for product.

12.3 Persistence and degradability: No information available for product.

12.4 Results of PBT assessment: No information available for product

12.5 Other adverse effects: No information available for product

13. DISPOSAL CONSIDERATIONS

13.1 Appropriate disposal / Product: Do not contaminate drains, soil or surface waters with this material or its container. Reduce waste by attempting to utilize product completely. Dispose of this container and its contents in accordance with all local, state, and federal regulations. Do not reuse or refill.

13.2 Waste codes / waste designations according to EWC / AVV: 070208

13.3 Appropriate packaging: NA

13.4 Additional information: Prior to disposal 3D Systems recommends consulting an approved waste disposal firm to ensure regulatory compliance.

14. TRANSPORT INFORMATION

14.1 Land transport (DOT/ADR/RID/GGVSE):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Technical name: (Tricyclodecane Dimethanol Diacrylate)

Class: 9 Packaging group: III

Marine pollutant: yes

Contains: Acrylates

14.2 Sea transport (IMDG-Code/GGVSee):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Technical name: (Tricyclodecane Dimethanol Diacrylate)

Class: 9 Packaging group: III

Marine pollutant: yes

Contains: Acrylates

14.3 Air transport (ICAO-IATA/DGR):

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Technical name: (Tricyclodecane Dimethanol Diacrylate)

Class: 9 Packaging group: III

Marine pollutant: yes

Contains: Acrylates

14.4 US Department of Transportation (DOT)

UN Number: 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Technical name: (Tricyclodecane Dimethanol Diacrylate)

Class: 9 Packaging group: III

Marine pollutant: yes

Contains: Acrylates

Safety Data Sheet

VisiJet® M2S-HT250

Revision Date: June 29, 2020

15. REGULATORY INFORMATION

15.1 EU regulations

EINEC/ELINCS/NLP: Research and development use only.

REACH Annex XVII: None listed

15.2 EU National regulations

Wassergefährdungsklasse (water hazard class, Germany): WGK 2: Hazard to waters

15.3 US FEDERAL

TSCA: All components listed or exempt from listing

TSCA - 5(a) Significant New Use Rule List of Chemicals: None

US. Toxic Substances Control Act (TSCA) Section 12(b): None

SARA 302 EHS List (40 CFR 355 Appendix A): None listed

SARA 313 (40 CFR 372.65): None listed

CERCLA (40 CFR 302.4): None listed

SARA 302 EHS List (40 CFR 355 Appendix A): None listed

SARA 313 (40 CFR 372.65): None listed

CERCLA (40 CFR 302.4): None listed

15.4 International regulations: All components of this product are registered or exempt from registration according to chemical regulations in Australia, Canada, China, European Union, Japan, Taiwan, New Zealand, Philippines, South Korea, Switzerland, USA chemical inventories.

15.5 Japanese regulations

| | |
|--|--|
| Chemical Risk Information platform (CHRIP) | not applicable |
| Industrial Health and Safety Law | not applicable |
| Hazardous material | not applicable |
| Organic solvent poison prevention rule | not applicable |
| Ordinance on prevention of hazard due to specified chemical substances | not applicable |
| Lead Poisoning Prevention Rule | not applicable |
| Poison and Deleterious Substance Control law | not applicable |
| PRTR and Promotion of Chemical Management law (PRTR Law) | no listed components |
| Fire Services Act | Category 4, Class 3, oil |
| Explosives Law | not applicable |
| High pressure gas safety law | not applicable |
| Export Trade Control Order | not applicable |
| Waste Disposal and Public Cleaning Law | applicable. Before disposal, consult an approved waste disposal operative to ensure regulatory compliance. |

16. OTHER INFORMATION

16.1 Relevant Hazard Statements (number and full text) referred to in sections 2 and 3 (according to (EC) No. 1272/2008):

H319: Causes serious eye irritation

H315: Causes skin irritation

H361f: Suspected of damaging fertility or the unborn child

H335: May cause respiratory irritation

H401: Toxic to aquatic life

H317: May cause an allergic skin reaction

H411: Toxic to aquatic life with long-lasting effects

H412: Harmful to aquatic life with long-lasting effects

16.2 Further information:

SDS Creation Date: May 23, 2019

SDS Revision #: -01-A

SDS Revision Date: June 29, 2020

Reason for Revision: Update section 1, 2, 3, 9, 14, 15, 16.

Safety Data Sheet

VisiJet® M2S-HT250

Revision Date: June 29, 2020

www.3dsystems.com

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

+44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its products shall be for the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. 3D Systems, Inc. recommends that you periodically check www.3dsystems.com to make sure you are using the most current safety data sheet.

© Copyright 2019 - 2020 by 3D Systems, Inc. All rights reserved. 3D Systems, the 3D logo, ProJet and VisiJet are registered trademarks of 3D Systems, Inc.