

## Safety Data Sheet

### Accura® ABS Black (SL 7820)

Revision Date: November 07, 2019

#### 1. IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING

##### 1.1 Identification of the mixture: Accura® ABS Black (SL 7820)

**1.2 Use of the preparation:** For use with SLA Systems

##### 1.3 Company/undertaking identification:

3D Systems, Inc.  
333 Three D Systems Circle  
Rock Hill, South Carolina U.S.A.  
Phone: 803.326.3900 or  
Toll-free Phone: 800.793.3669  
e-mail: [moreinfo@3dsystems.com](mailto:moreinfo@3dsystems.com)  
Chemical Emergency:  
800.424.9300 – Chemtrec

3D Systems Europe Ltd.  
Mark House, Mark Road  
Hemel Hempstead  
Herts HP2 7 United Kingdom  
Phone: +44 144-2282600  
e-mail: [moreinfo@3dsystems.com](mailto:moreinfo@3dsystems.com)  
Chemical Emergency:  
+1 703.527.3887 - Chemtrec

3D Systems / Australia  
5 Lynch Street  
Hawthorn, VIC 3122  
+1 03 9819-4422  
e-mail: [moreinfo@3dsystems.com](mailto:moreinfo@3dsystems.com)  
Chemical Emergency:  
+(61) 29037.2994 – Aus Chemtrec

#### 2. HAZARDS IDENTIFICATION

##### 2.1 Classification

**GHS : Regulation (EC) No. 1272/2008, HazCom 2012:**

**Physical Hazard:**  
None

##### Health Hazard:

Skin Corrosion/Irritation	Category 2	H315
Serious Eye Damage/Eye Irritation	Category 2	H319
Skin Sensitization	Category 1	H317

##### Environmental Hazard:

Chronic Aquatic Toxicity	Category 2	H411
--------------------------	------------	------

##### 2.2 Label Elements

**Regulation (EC) No, 1272/2008:**

**Hazard pictograms and signal word:**



**GHS07**



**GHS09**

**Signal word: Warning**

**Hazard determining components of labelling:**

4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane

##### Hazard statements:

H319: Causes serious eye irritation  
H315: Causes skin irritation  
H317: May cause an allergic skin reaction  
H411: Toxic to aquatic life with long lasting effects

## Safety Data Sheet

### Accura® ABS Black (SL 7820)

Revision Date: November 07, 2019

#### Prevention:

P260: Do not breathe dust/fume/gas/mist/vapors/spray.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P264: Wash contaminated skin thoroughly after handling.  
 P270: Do not eat, drink or smoke when using this product.  
 P273: Avoid release to the environment.

#### Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water  
 P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P362: Take off contaminated clothing and wash before reuse  
 P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310: Immediately call a POISON CENTER or doctor/physician.

#### Storage:

P410 + P403: Protect from sunlight. Store in a well-ventilated place.

#### Disposal:

P501: Dispose of contents/container in accordance with local/state/regional regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Chemical characterization:

**Description:** Organic mixture

#### 3.2 Dangerous components:

Chemical name	CAS-No	EC-No	%	Classification
				Regulation (EC) 1272/2008
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	500-070-7	40-50	Skin Sensitization Category 1 - H317
3-ethyl-3-hydroxymethyl-oxetane	3047-32-3	221-254-0	10-20	Serious Eye Dam/Eye Irritation Cat 2 - H319
Tricyclodecane dimethanol diacrylate	42594-17-2	255-901-3	15-30	Skin Sensitization Category 1 - H317 Aquatic Chronic Category 2 - H411
Pentaerythritol tetraacrylate	Proprietary	Proprietary	1-10	Serious Eye Dam/Eye Irritation Cat 2 - H319 Skin Corrosion/Irritation Category 2 - H315 Aquatic Chronic Category 2 - H411

### 4. FIRST AID MEASURES

**4.1 General Information:** Ensure that eyewash stations and safety showers are close to the workstation location.

**4.2 In case of inhalation:** May cause respiratory irritation. Move affected person to fresh air. If respiratory irritation occurs, if breathing becomes difficult seek medical attention immediately.

**4.3 In case of skin contact:** May cause irritation or sensitization by skin contact, including redness and/or swelling. Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.

**4.4 In case of eye contact:** Irritating to eyes. Causes redness, swelling and pain. Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.

**4.5 In case of ingestion:** Irritating to mouth, throat and stomach. If ingested, drink plenty of water and seek immediate medical attention. Do not induce vomiting.

## Safety Data Sheet

### Accura® ABS Black (SL 7820)

Revision Date: November 07, 2019

---

**4.6 Self-protection of the first aider:** Put on appropriate protective equipment (see section 8). Move exposed person to fresh air. Remove contaminated clothing and shoes.

---

#### 5. FIRE-FIGHTING MEASURES

**5.1 Suitable extinguishing media:** Water mist, dry chemical, carbon dioxide, or appropriate foam.

**5.2 Extinguishing media which must not be used for safety reasons:** High volume water jet.

**5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:** Thermal decomposition products can include CO<sub>2</sub>, CO and smoke.

**5.4 Special protective equipment for fire-fighters:** Wear full protective clothing, including helmet, self-contained positive-pressure or pressure demand breathing apparatus, protective clothing and facemask.

**5.5 Additional information:** Move container from area if it can be done without risk. Cool containers with water spray. Avoid inhalation of material or combustion by-products.

---

#### 6. ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions:** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing. Consult expert immediately.

**6.2 Environmental precautions:** Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. In case of contamination of aquatic environment inform local authorities.

**6.3 Methods for cleaning up:** Wear appropriate protective equipment and clothing. Absorb spillage with suitable absorbent materials. Place all waste in an appropriate container for disposal. The material and its container must be disposed of as hazardous waste. Keep away from sources of ignition.

---

#### 7. HANDLING AND STORAGE

**7.1 Handling** Provide adequate ventilation. Use suitable protective equipment. Avoid contact with skin and eyes. Do not breathe vapors or mist. Avoid ignition sources. Do not allow to enter drains or watercourses.

**7.2 Storage:** Store sealed in the original container at room temperature. Keep this material indoors in a cool, dry, well ventilated place. Store out of direct sunlight or UV light sources. Storage Temperature: below 35 °C / 95 °F. Storage class 10, environmentally hazardous liquids.

---

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

##### 8.1 Exposure limit values:

General Product Information: No occupational exposure limits (PEL/TWA) have been established for this product.

##### 8.2 Exposure controls

**Technical measures to prevent exposure:** Use local exhaust ventilation.

**Instructual measures to prevent exposure:** When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.

##### Personal protection equipment:

**Respiratory protection:** If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided (e.g. 3M 6000 with organic vapor cartridge A2 or half mask 3M 4251).

**Hand protection:** Use impervious nitrile gloves.

**Eye protection:** Wear safety glasses or chemical goggles.

**Body protection:** Use apron and closed shoes.

---

## Safety Data Sheet

### Accura® ABS Black (SL 7820)

Revision Date: November 07, 2019

---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1 Appearance:

**Physical state:** Liquid

**Colour:** White

**Odour:** Mild

##### 9.2 Important health, safety and environmental information

<b>pH (20 °C):</b>	NA
<b>Melting point/range (°C):</b>	NA
<b>Boiling point/range (°C):</b>	NA
<b>Flash point (°C):</b>	131°C
<b>Ignition temperature (°C):</b>	NA
<b>Vapour pressure (°C):</b>	NA
<b>Density (g/cm<sup>3</sup>):</b>	1.08 g/cm <sup>3</sup>
<b>Bulk density (kg/m<sup>3</sup>):</b>	NA
<b>Water solubility (20°C in g/l):</b>	slightly soluble
<b>Viscosity, dynamic (mPa s):</b>	~260 (30°C)
<b>Dust explosion hazard:</b>	NA
<b>Explosion limits:</b>	NA

---

#### 10. STABILITY AND REACTIVITY

**10.1 Conditions to avoid:** Avoid exposure to heat and light. Take necessary actions to avoid static electricity discharge.

**10.2 Materials to avoid:** Oxidizing materials, strong acids and strong bases.

**10.3 Hazardous decomposition products:** Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

---

#### 11. TOXICOLOGICAL INFORMATION

**11.1 Toxicokinetics, metabolism and distribution:** NA

##### 11.2 Acute effects (toxicity tests)

Component	LD <sub>50</sub> Oral	LD <sub>50</sub> Dermal
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	>5300 mg/kg (rat)	>2000 mg/kg (rabbit)
Sulfonium salt mixture	>5000mg/kg (rat)	>2000 mg/kg(rat)
3-ethyl-3-hydroxymethyl-oxetane	>2000 mg/kg (rat)	NA

**Irritant and corrosive effects:** Irritating

**Irritation to respiratory tract:** NA

**Sensitisation:** Causes sensitisation

**11.3 Experiences made in practice:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**11.4 General remarks:** Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

## Safety Data Sheet

### Accura<sup>®</sup> ABS Black (SL 7820)

Revision Date: November 07, 2019

#### 12. Ecological information

**12.1 Ecotoxicity:** The aquatic toxicity of the product is unknown; however based on components, it is predicted that this material may be toxic to aquatic organisms or cause long-term adverse effects in the aquatic environment. Prevent contamination of soil, drains and surface waters.

Component	Data
Sulfonium salt mixture	EC50/48h – 0.2 mg/l (daphnia) LC50/96h- 2.3 mg/l(poecilia reticulata)
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC/EC/IC 50: 1-10 mg/l

**12.2 Mobility:** No information available for product.

**12.3 Persistence and degradability:** No information available for product.

**12.4 Results of PBT assessment:** No information available for product

**12.5 Other adverse effects:** No information available for product

#### 13. DISPOSAL CONSIDERATIONS

**13.1 Appropriate disposal / Product:** Do not contaminate drains, soil or surface waters with this material or its container. Reduce waste by attempting to utilize product completely. Dispose of this container and its contents in accordance with all local, state, and federal regulations. Do not reuse or refill.

**13.2 Waste codes / waste designations according to EWC / AVV:** 070208

**13.3 Appropriate packaging:** NA

**13.4 Additional information:** Prior to disposal 3D Systems recommends consulting an approved waste disposal firm to ensure regulatory compliance.

#### 14. TRANSPORT INFORMATION

##### 14.1 Land transport (ADR/RID/GGVSE):

Official transport designation: Environmentally hazardous substance, liquid N.O.S. (Acrylic Polymers -Other)

UN-No.: 3082

Class: 9

Classification Code: M6

Packing group: III

Hazard label: 9

Risk No: 90

Tunnel restriction code: 3 ( E )

Contains. Epoxy resin

##### 14.2 Sea transport (IMDG-Code/GGVSee):

Official transport designation: Environmentally hazardous substance, liquid N.O.S. (Acrylic Polymers -Other)

UN-No.: 3082

Class: 9

Packing group: III

Hazard label: 9

Contains. Epoxy resin

##### 14.3 Air transport (ICAO-IATA/DGR):

Official transport designation: Environmentally hazardous substance, liquid N.O.S. (Acrylic Polymers -Other)

UN-No.: 3082

Class: 9

Packing group: III

Hazard label: 9

Contains. Epoxy resin

## Safety Data Sheet

### Accura® ABS Black (SL 7820)

Revision Date: November 07, 2019

---

#### 14.4 Department of Transportation (DOT)

Official transport designation: Environmentally hazardous substance, liquid N.O.S. (Acrylic Polymers -Other)

UN-No.: 3082

Class: 9

Packing group: III

Hazard label: 9

Contains. Epoxy resin

---

#### 15. REGULATORY INFORMATION

##### 15.1 EU regulations

EINEC/ELINCS/NLP: All materials are listed

REACH Annex XVII: None listed

##### 15.2 EU- National regulations

Wassergefährdungsklasse (water hazard class, Germany): WGK 2: Hazard to waters

##### 15.3 US FEDERAL

TSCA: All materials are listed or exempt from listing

SARA 302 EHS List (40 CFR 355 Appendix A): None listed

SARA 313 (40 CFR 372.65): Antimony Compounds (category N010)

CERCLA (40 CFR 302.4): None listed

##### 15.4 Australian regulations

SUSDP, Industrial Chemicals Act 1989:

Australian Inventory of Chemical Substances, AICS: Listed

---

#### OTHER INFORMATION

##### 16.1 Relevant Hazard Statements (number and full text) referred to in sections 2 and 3 (according to (EC) No. 1272/2008):

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H319: Cause Serious Eye Irritation

H400: Very toxic to aquatic life

H410: Very toxic to aquatic life with long-lasting effects

H411: Toxic to aquatic life with long-lasting effects

##### 16.2 Further information:

SDS Creation Date: .....December 18, 2012

SDS Revision #: .....04-A

SDS Revision Date: .....November 07, 2019

Reason for Revision: .....Update header, section 1, 2, 3, 8, 9, 14, 15, 16.

[www.3dsystems.com](http://www.3dsystems.com)

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

+44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its products shall be for the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. 3D Systems, Inc. recommends that you periodically check [www.3dsystems.com](http://www.3dsystems.com) to make sure you are using the most current safety data sheet.

© Copyright 2012-2019 by 3D Systems, Inc. All rights reserved. 3D Systems, the 3D logo and Accura are registered trademarks of 3D Systems, Inc.